

Deform-Nut®

SERIE TC/K • TC/KZ

S E R I E S



THREADED TUBULAR RIVET NUT WITH ROUND HEAD IN STAINLESS STEEL 316

APPLICATION
On boxed and tubular sections, metal sheets, other materials.
ASSEMBLY
By specific manual and pneumatic tools.

CODE		Grip range	Total length	Metrical thread	Shaft Ø	Head Ø	thicknesses	Hole Ø
		(s)	(l)	(d1)	(d)	(d3)	(l1)	(d5) +0,15 0
TC M 4/K	TC M 4/KZ	0,5 ÷ 2,0	12,0	M 4	6,0	9,0	1,0	6,0
TC M 5/K	TC M 5/KZ	0,5 ÷ 3,0	12,5	M 5	7,0	10,0	1,0	7,0
TC M 6/K	TC M 6/KZ	0,5 ÷ 3,0	16,0	M 6	9,0	12,0	1,5	9,0
TC/L M 6/K	TC/L M 6/KZ	3,0 ÷ 5,0	18,0					
TC M 8/K	TC M 8/KZ	0,5 ÷ 3,0	17,5	M 8	11,0	15,0	1,5	11,0
TC M10/K	TC M10/KZ	0,8 ÷ 3,5	23,0	M 10	13,0	17,0	1,5	13,0

SERIES TC/K (plain)

MATERIAL

Stainless steel AISI 316 (on demand)

FINITURA

Natural state

EXAMPLE OF CODE DESIGNATION

Threaded tubular rivet nuts with round head, grip thicknesses 2,0 mm, M 6 thread, stainless steel aisi 316: **TC M 6/K**

SERIES TC/KZ (knurled)

MATERIAL

Stainless steel AISI 316 (on demand)

FINITURA

Natural state

EXAMPLE OF CODE DESIGNATION

Threaded tubular rivet nuts with round head and knurled body, grip thicknesses 2,0 mm, M 6 thread, stainless steel aisi 316: **TC M 6/KZ**

Juno Industries BVBA - Stoktevijver 22 - 9930 Zomergem/België/Belgique
 Tel/tél: (0)9/395.95.90 - Fax: (0)9/395.95.91 - co@junoindustries.eu

Non binding dimensions, expressed in mm.

