

Deform-Nut®

SERIE E TC/TL/CH

THREADED TUBULAR CLOSED END RIVET NUT WITH LARGE ROUND HEAD AND HEXAGONAL SHANK



APPLICATION

On boxed and tubular sections, metal sheets, other materials.

ASSEMBLY

By specific manual or pneumatic tools.

CODE	Grip range	Total lenght	Metrical thread	Hexagonal shank	Head Ø	Head thicknesses	Hexagonal hole	Rear lenght
	(s)	(l)	(d1) 6H	(ch)	(d3)	(l1)	(d5) + 0,15 0	(l2) *
E TC/TL/CH M 3/8S	0,5 ÷ 2,0	13	M 3	5	9	0,8	5	9,5
E TC/TL/LCH M 3/8S	2,0 ÷ 3,5	14,5						
E TC/TL/CH M 4/8S	0,5 ÷ 2,0	15	M 4	6	10	0,8	6	11
E TC/TL/LCH M 4/8S	2,0 ÷ 4,0	17						
E TC/TL/CH M 5/8S	0,5 ÷ 2,5	18	M 5	7	11	1	7	12,5
E TC/TL/LCH M 5/8S	2,5 ÷ 4,5	20						
E TC/TL/CH M 6/8S	0,5 ÷ 3,0	22,8	M 6	9	13	1,5	9	16
E TC/TL/LCH M 6/8S	3,0 ÷ 5,5	25,3						
E TC/TL/CH M 8/8S	0,5 ÷ 3,5	26	M 8	11	16	1,5	11	18
E TC/TL/LCH M 8/8S	3,5 ÷ 6,0	28,5						
E TC/TL/CH M 10/8S	0,5 ÷ 3,5	31	M 10	13	18	1,8	13	23
E TC/TL/LCH M 10/8S	3,5 ÷ 6,0	33,5						
E TC/TL/CH M 12/8S	0,5 ÷ 3,5	38,5	M 12	16	23	2	16	29
E TC/TL/LCH M 12/8S	3,5 ÷ 6,5	41,5						

* Dimensions measured on average thicknesses. Variable according to s dimension.

Non binding dimensions, expressed in mm.

MATERIAL

Steel nr. 1.0303

SURFACE TREATMENT

White zinc plating

THREAD TOLERANCE

Metrical tolerance ISO 6H

EXAMPLE OF CODE DESIGNATION

Threaded tubular closed end rivet nut with large round head and hexagonal shank, grip thicknesses 2,0 mm, M 6 thread, steel: **E TC/TL/CH M 6/8S**

Juno Industries - Stoktevijver 22 - 9930 Zomergem/België/Belgique
Tel/tél: (0)9/395.95.90 - Fax: (0)9/395.95.91 - co@junoindustries.eu

