

Deform-Nut®

SERIE 10446

THREADED TUBULAR CLOSED END RIVET NUT WITH ROUND HEAD
AND HEXAGONAL SHANK



APPLICATION
On boxed and tubular sections, metal sheets, other materials.
ASSEMBLY
By specific manual or pneumatic tools.

Ref. UNI 10446 standard

CODE	Grip range	Total lenght	Metrical thread	Hexagonal shank	Head Ø	Head thicknesses	Hexagonal hole	Rear lenght
	(s)	(l)	(d1) 6H	(ch)	(d3)	(l1)	(d5) + 0,15 0	(l2) *
**10446A1/ M 3/_	0,5 ÷ 2,0	13	M 3	5	8	0,8	5	9,5
**10446B1/ M 3/_	2,0 ÷ 3,5	14,5						
10446A1/ M 4/_	0,5 ÷ 2,0	15	M 4	6	9	0,8	6	11
10446B1/ M 4/_	2,0 ÷ 4,0	17						
10446A1/ M 5/_	0,5 ÷ 2,5	18	M 5	7	10	1	7	12,5
10446B1/ M 5/_	2,5 ÷ 4,5	20						
10446A1/ M 6/_	0,5 ÷ 3,0	22,5	M 6	9	12	1,2	9	16
10446B1/ M 6/_	3,0 ÷ 5,5	25						
10446A1/ M 8/_	0,5 ÷ 3,5	25	M 8	11	14	1,3	11	17,5
10446B1/ M 8/_	3,5 ÷ 6,0	27,5						
10446A1/ M 10/_	0,5 ÷ 3,5	30,5	M 10	13	17	1,7	13	21,5
10446B1/ M 10/_	3,5 ÷ 6,0	33						

** No UNI standard.

* Dimensions measured on average thicknesses. Variable according to s dimension.

Non binding dimensions, expressed in mm.

MATERIAL

Steel nr. 1.0303

/ ____ / ____ / 8

Stainless steel nr. 1.4567 (excluding thread M3)

/ ____ / ____ / X

SURFACE TREATMENT

Steel rivet nuts: white zinc plating

- Stainless steel rivet nuts: natural state

THREAD TOLERANCE

Metrical tolerance ISO 6H

EXAMPLE OF CODE DESIGNATION

Threaded tubular closed end rivet nut with round head and hexagonal shank, grip thicknesses 2,0 mm, M6 thread, stainless steel: **10446A1 M6/X**

Juno Industries - Stoktevijver 22 - 9930 Zomergem/België/Belgique
Tel/tél: (0)9/395.95.90 - Fax: (0)9/395.95.91 - co@junoindustries.eu

